

2665 WC


**PCT**WORLD INTELLECTUAL PROPERTY ORGANIZATION  
International Bureau

## INTERNATIONAL APPLICATION PUBLISHED UNDER THE PATENT COOPERATION TREATY (PCT)

<b>(51) International Patent Classification <sup>7</sup>:</b> <b>B66B 11/08</b>	<b>A1</b>	<b>(11) International Publication Number:</b> <b>WO 00/44664</b> <b>(43) International Publication Date:</b> 3 August 2000 (03.08.00)
<b>(21) International Application Number:</b> PCT/FI00/00049 <b>(22) International Filing Date:</b> 25 January 2000 (25.01.00)  <b>(30) Priority Data:</b> 990152 27 January 1999 (27.01.99) FI 99119565.2 1 October 1999 (01.10.99) EP  <b>(71) Applicant (for all designated States except US):</b> KONE CORPORATION [FI/FI]; Kartanontie 1, FIN-00330 Helsinki (FI).  <b>(72) Inventors; and</b> <b>(75) Inventors/Applicants (for US only):</b> ORRMAN, Jaakko [FI/FI]; Tunturikatu 13 A 15, FIN-00100 Helsinki (FI). MUSTALAHTI, Jorma [FI/FI]; Raivaajantie 13, FIN-05620 Hyvinkää (FI).  <b>(74) Agent:</b> KONE CORPORATION/PATENT DEPARTMENT, P.O. Box 677, FIN-05801 Hyvinkää (FI).		<b>(81) Designated States:</b> AE, AL, AM, AT, AU, AZ, BA, BB, BG, BR, BY, CA, CH, CN, CR, CU, CZ, DE, DK, DM, EE, ES, FI, GB, GD, GE, GH, GM, HR, HU, ID, IL, IN, IS, JP, KE, KG, KP, KR, KZ, LC, LK, LR, LS, LT, LU, LV, MA, MD, MG, MK, MN, MW, MX, NO, NZ, PL, PT, RO, RU, SD, SE, SG, SI, SK, SL, TJ, TM, TR, TT, TZ, UA, UG, US, UZ, VN, YU, ZA, ZW, ARIPO patent (GH, GM, KE, LS, MW, SD, SL, SZ, TZ, UG, ZW), Eurasian patent (AM, AZ, BY, KG, KZ, MD, RU, TJ, TM), European patent (AT, BE, CH, CY, DE, DK, ES, FI, FR, GB, GR, IE, IT, LU, MC, NL, PT, SE), OAPI patent (BF, BJ, CF, CG, CI, CM, GA, GN, GW, ML, MR, NE, SN, TD, TG).  <b>Published</b> With international search report. Before the expiration of the time limit for amending the claims and to be republished in the event of the receipt of amendments.

**(54) Title:** TRACTION SHEAVE ELEVATOR**(57) Abstract**

In a traction sheave elevator, the elevator car is suspended on hoisting ropes by means of a diverting pulley. The diverting pulley used to suspend the elevator car on the hoisting ropes is mounted on one side of the elevator car.



**FOR THE PURPOSES OF INFORMATION ONLY**

Codes used to identify States party to the PCT on the front pages of pamphlets publishing international applications under the PCT.

AL	Albania	ES	Spain	LS	Lesotho	SI	Slovenia
AM	Armenia	FI	Finland	LT	Lithuania	SK	Slovakia
AT	Austria	FR	France	LU	Luxembourg	SN	Senegal
AU	Australia	GA	Gabon	LV	Latvia	SZ	Swaziland
AZ	Azerbaijan	GB	United Kingdom	MC	Monaco	TD	Chad
BA	Bosnia and Herzegovina	GE	Georgia	MD	Republic of Moldova	TG	Togo
BB	Barbados	GH	Ghana	MG	Madagascar	TJ	Tajikistan
BE	Belgium	GN	Guinea	MK	The former Yugoslav Republic of Macedonia	TM	Turkmenistan
BF	Burkina Faso	GR	Greece	ML	Mali	TR	Turkey
BG	Bulgaria	HU	Hungary	MN	Mongolia	TT	Trinidad and Tobago
BJ	Benin	IE	Ireland	MR	Mauritania	UA	Ukraine
BR	Brazil	IL	Israel	MW	Malawi	UG	Uganda
BY	Belarus	IS	Iceland	MX	Mexico	US	United States of America
CA	Canada	IT	Italy	NE	Niger	UZ	Uzbekistan
CF	Central African Republic	JP	Japan	NL	Netherlands	VN	Viet Nam
CG	Congo	KE	Kenya	NO	Norway	YU	Yugoslavia
CH	Switzerland	KG	Kyrgyzstan	NZ	New Zealand	ZW	Zimbabwe
CI	Côte d'Ivoire	KP	Democratic People's Republic of Korea	PL	Poland		
CM	Cameroon	KR	Republic of Korea	PT	Portugal		
CN	China	KZ	Kazakhstan	RO	Romania		
CU	Cuba	LC	Saint Lucia	RU	Russian Federation		
CZ	Czech Republic	LI	Liechtenstein	SD	Sudan		
DE	Germany	LK	Sri Lanka	SE	Sweden		
DK	Denmark	LR	Liberia	SG	Singapore		
EE	Estonia						

## TRACTION SHEAVE ELEVATOR

The present invention relates to a traction sheave elevator as defined in the preamble of claim 1, an  
5 elevator car as defined in the preamble of claim 16, a method as defined in the preamble of claim 17 and use of a diverting pulley as defined in the preamble of claim 18 for suspending an elevator car on hoisting ropes.

10

In prior art, specification EP 0 631 967 A2 presents a traction sheave elevator without machine room, in which an elevator car moving in an elevator shaft is guided by vertical car guide rails while the counter-  
15 weight moves along guide rails placed on the same side of the elevator car as the car guide rails. Such a suspension arrangement, in which all guide rails are placed as a compact structure on one side of the elevator car, is called piggyback suspension. The drive  
20 motor, provided with a traction sheave, is mounted in the upper part of the guide rails. Connected to the elevator car are two car rope pulleys, placed under the bottom of the elevator car at opposite edges. The first end of the rope is attached to a fixed top  
25 structure in the upper part of the elevator shaft, on the same side of the elevator car as where the car and counterweight guide rails are located. From the anchorage of its first end, the rope is passed down via a counterweight rope pulley attached to the counter-  
30 weight, from where it is deflected up and passed to the traction sheave of the drive motor, from where it is further deflected down and passed around two rope pulleys mounted on the elevator car, so that the rope passes under the elevator car by one side, where the  
35 guide rails are located, to the other side and further up to a fixed top structure, to which the other end of

the rope is fixed and which is located on the other side of the elevator car relative to the location of the car and counterweight guide rails. In this way, an advantageous 2:1 suspension arrangement is achieved, allowing the machinery to be designed in accordance with a lower torque requirement.

A problem with the prior-art elevator is that the two rope pulleys below the elevator car require a certain space in the vertical direction of the elevator. This is a problem particularly in buildings where it is not possible to extend the elevator shaft substantially below the level of the lowest floor to provide a sufficient space for the rope pulleys under the elevator car when the car is at the bottom floor. This problem is often encountered in conjunction with the modernization of old elevator shafts where a scanty space has been provided at the bottom end of the shaft. In old buildings, building a new elevator shaft or extending the old one to a level clearly below the bottom floor is a significant cost factor. Similarly, an insufficient head room at the top end may be an obstacle to mounting car rope pulleys on the top of the elevator car. As for new buildings, an elevator shaft that takes up as little space in the vertical direction as possible would be an advantage.

A further problem with the prior-art elevator is that, on the opposite side of the elevator car relative to the side on which the car and counterweight guide rails are located, a sufficient space for rope passage must be provided between the shaft wall and the wall of the elevator car, which constitutes a limitation of the widthwise dimension of the elevator car, preventing effective utilization of the cross-sectional area of the elevator shaft.

The object of the invention is to eliminate the problems mentioned above.

5 A specific object of the invention is to disclose an elevator that is as compact as possible, requiring as little space as possible in the elevator shaft in both vertical and horizontal directions so as to allow as efficient shaft space utilization as possible. A further  
10 object of the invention is to disclose an elevator which is well suited for use both in new buildings and in old buildings for the modernization of elevator solutions in existing elevator shafts or even as an elevator for which a shaft is built afterwards in an  
15 existing building.

As for the features characteristic of the traction sheave elevator, elevator car and method of the invention and the use of a diverting pulley according  
20 to the invention, reference is made to the claims.

The elevator of the invention comprises car guide rails disposed vertically in an elevator shaft; an elevator car designed to move along the car guide  
25 rails; counterweight guide rails disposed in the elevator shaft on the same side of the elevator car as the car guide rails; a counterweight designed to move along the counterweight guide rails; an upper rope pulley mounted on a fixed top structure in the upper  
30 part of the elevator shaft; a car rope pulley connected to the elevator car; a counterweight rope pulley connected to the counterweight; a drive motor disposed in the elevator shaft to drive one of the rope pulleys; and a rope whose first end is attached to a  
35 fixed top structure in the upper part of the elevator shaft on the same side of the elevator car with the

car and counterweight guide rails, from where the rope is passed via the counterweight rope pulley, upper rope pulley and car rope pulley, and whose second end is attached to a fixed top structure.

5

According to the invention, the second end of the rope is attached to a fixed top structure on the same side of the elevator car as the first end. The car rope pulley is rotatably mounted with bearings at the side  
10 of the elevator car on the same side of the elevator car as the car and counterweight guide rails.

'Fixed top structure' refers to a fixed structure in the upper part of the elevator shaft near the ceiling,  
15 or to the top of the elevator shaft, the guide rails in the upper part of the shaft or corresponding structures.

The invention has the advantage that it makes it possible to build an elevator that is as compact as possible in the vertical direction and, on the other hand, as large as possible in relation to the cross-sectional area of the elevator shaft. The entire machinery as well as the rope and rope pulleys can be  
25 located on one side of the elevator car as a compact package. Furthermore, the invention has the advantage that, in addition to new buildings, it is suited for use in modernization projects. A further advantage is that the space at the bottom end of the elevator shaft  
30 can be constructed to dimensions as small as possible. In addition, the invention has the advantage that it is suited for use as an elevator without machine room, with the elevator machine mounted in the elevator shaft.

35

In an embodiment of the elevator, the car guide rails and counterweight guide rails are attached to each other and to the wall of the elevator shaft, arranged side by side parallel to each other, the counterweight  
5 guide rails being placed between the wall of the elevator shaft and the car guide rails.

In an embodiment of the elevator, the distance between the counterweight guide rails is equal to the distance  
10 between the car guide rails. The conventional design of the counterweight is such that the mass of the counterweight equals the car weight when the car is empty, added by half the specified load. By disposing the counterweight guide rails at a maximal distance  
15 from each other, the width of the counterweight can be maximized, and consequently a compact counterweight with a short vertical dimension is achieved.

In an embodiment of the elevator, the upper rope pulley is the drive wheel connected to the drive motor.  
20 In this case, the drive motor is mounted on the car guide rails and/or counterweight guide rails in the upper part of the elevator shaft, which means that the elevator has no machine room. It is also possible to  
25 use one of the other rope pulleys mentioned as a drive wheel.

In an embodiment of the elevator, the elevator comprises an L-shaped frame structure attached to the  
30 car, extending on the side wall of the elevator car on that side where the car guide rails and counterweight guide rails are located and under the bottom of the elevator car. The car rope pulley and the guide elements acting together with the car guide rails are  
35 connected to this frame structure.

In an embodiment of the elevator, the car rope pulley is placed in the lower part of the elevator car near its bottom.

- 5 The car rope pulley is preferably disposed inside the space defined by the elevator car and the frame structure to achieve compact space utilization.

10 In an embodiment of the elevator, a vertical tangent to the upper rope pulley is substantially aligned with a vertical tangent to the counterweight rope pulley, in which case the rope portion between them is substantially vertical. Correspondingly, a vertical tangent to the upper rope pulley is substantially aligned  
15 with a vertical tangent to the car rope pulley, so the rope portion between these pulleys, too, is substantially vertical.

In an embodiment of the elevator, the middle plane of  
20 rotation of the counterweight rope pulley is parallel to the middle plane of rotation of the car rope pulley. The middle plane of rotation of the upper rope pulley is at an angle to the middle planes of rotation of the car rope pulley and counterweight rope pulley.  
25 In this case, the middle plane of rotation of the car rope pulley may be parallel to the side wall of the elevator car, or alternatively the middle plane of rotation of the car rope pulley may be at an angle to the side wall of the elevator car.

30

In an embodiment of the elevator, the drive motor is a permanent magnet synchronous motor and the upper rope pulley is integrated with the rotor of the motor.

35 In a traction sheave elevator without machine room, the use of a diverting pulley mounted on the side of



the elevator car to suspend the car on the hoisting ropes allows the elevator to be installed in an elevator shaft having a height dimension smaller than the conventional height. In principle, this solution can  
5 be used both in elevators with machine room above and in elevators with machine room below. To economize on the cross-sectional area of the elevator shaft, the diverting pulley attached to the elevator car must be parallel to the car wall or only moderately askew  
10 relative to the wall. An economical solution is to mount the hoisting machine on a fixed structure of the elevator shaft. However, in elevators with machine room below, the amount of material including diverting pulleys and ropes is larger and, as the number of di-  
15 verting pulleys and rope portions between rope pulleys is larger, a solution with machine room below may result in an elevator having a slightly larger height dimension than an elevator with machine room above. When the suspension of the elevator is implemented us-  
20 ing a diverting pulley on the side of the elevator car, the height dimension can be best reduced by placing the drive machine at such a height in the elevator shaft that the elevator car can move to a position alongside the machine.

25

In the following, the invention will be described in detail by the aid of a few examples of its embodiments with reference to the attached drawing, wherein

30 Fig. 1 presents diagram representing an embodiment of the elevator of the invention as seen in an oblique top view,

Fig. 2 presents a diagrammatic top view of the eleva-  
35 tor in Fig. 1, and

Fig. 3 a diagrammatic top view of another embodiment of the elevator of the invention.

Fig. 1 presents a diagrammatic view of a traction  
5 sheave elevator with a car suspended according to the so-called piggyback principle. The car guide rails 1 are disposed vertically in the elevator shaft on one side relative to the elevator car and the elevator car 2 has been arranged to move along car guide rails 1.  
10 The counterweight guide rails 3 are disposed in the elevator shaft on the same side of the elevator car as the car guide rails 1. The car guide rails 1 and the counterweight guide rails 3 are attached to each other and to a wall 12 (not shown in Fig. 1, see Fig. 2) of  
15 the elevator shaft, mounted side by side close to each other in parallel directions so that the counterweight guide rails 3 are located between the car guide rails 1 and the wall 12 of the elevator shaft. The distance of the counterweight guide rails 3 from each other is  
20 equal to the distance of the car guide rails 1 from each other, so the counterweight 4 moving along the counterweight guide rails can be of a shape having a large width and a small length.

25 The drive motor 8 is mounted on a transverse support 17 connected to the upper ends of all four guide rails 1, 3. The drive motor 8 is a permanent magnet synchronous motor, the driving rope pulley 5 being integrated with its rotor.

30 Attached to the elevator car 2 is an L-shaped frame structure 13 extending along the side wall 14 of the elevator car 1 on that side where the car guide rails 1 and counterweight guide rails 3 are located and under  
35 the bottom 15 of the elevator car to support the car. Guide elements 16 acting together with the car

- guide rails 1 are connected to the frame structure 13. Connected to the frame structure 13 is also a car rope pulley 6. The car rope pulley 6 is located at the side of the elevator car 2 in its lower part on the same side of the elevator car 1 with the car guide rails 1 and counterweight guide rails 3 so that the car rope pulley 6 does not protrude below the car 1 or outside the frame structure 13.
- 10 The first end 10 of the rope 9 is attached to the support 17 between the guide rails 1, 3, from where it is passed down to the counterweight rope pulley 7 on the upper edge of the counterweight 4. From here, the rope is deflected back up and goes to the traction sheave 5
- 15 of the drive motor 8, from where it is again deflected downward and passed to the rope pulley 6 mounted on the side of the elevator car 2, from where it is deflected upward and passed to the anchorage of the second end 11 in the support 17 between the guide rails
- 20 1, 3. Thus, the elevator car is suspended on the rope loop between the traction sheave 5 and the rope end 11. All the rope pulleys 5, 6, 7 are located on the same side relative to the elevator car, so the rope 9 can run substantially entirely in the space between
- 25 the guide rails 1, 3.

For the sake of clarity, Fig. 1 shows only one rope, but it is obvious that the rope may comprise a bundle of ropes or a plurality of adjacent ropes, as is usually the case in elevators. Also, the rope pulleys 5, 6, 7 are presented as simple grooved wheels, but it is obvious that when a plurality of adjacent ropes are used, the rope pulleys are manifold or several rope pulleys may be placed side by side. The rope pulleys

30 may be provided with grooves of a semi-circular cross-

35

section, and the traction sheave may have undercut grooves to increase friction.

Fig. 3 and 4 illustrate two embodiments for the arrangement of the rope pulleys 5, 6, 7 relative to each other. In the drawings, the drive motor 8 and the driving rope pulley 5 are depicted with broken lines while the counterweight rope pulley 7 and the car rope pulley 6 are depicted with solid lines. In both embodiments, the aim has been to arrange the rope pulleys 5, 6, 7 in such a way that the rope will apply as little skewed pull to the rope wheel grooves as possible as it passes from one wheel rim to the next. Without the arrangement described below, skewed pull might occur when the counterweight rope pulley 7 is in a high position close to the traction sheave 5 and similarly when the car rope pulley 6 is close to the traction sheave 5.

In Fig. 3 and 4, skewed pull is eliminated by using an arrangement in which a vertical tangent to the driving rope pulley 5 is substantially aligned with a vertical tangent to the counterweight rope pulley 7, the rope portion between these pulleys being thus substantially vertical, and in which a tangent to the upper rope pulley 5 is substantially aligned with a vertical tangent to the car rope pulley 6, the rope portion 9 between these pulleys being likewise substantially vertical.

In Fig. 3, both the car rope pulley 6 and the counterweight rope pulley 7 are disposed in identical positions so that their middle planes of rotation are parallel to each other and at an angle to the middle plane of rotation of the traction sheave 5. The middle plane of rotation of the traction sheave 5 is parallel

to the side wall 14 of the elevator car and the shaft wall, whereas the middle planes of rotation of the car rope pulley 6 and counterweight rope pulley 7 are at an inclined angle to the side wall 14 of the elevator car and the shaft wall.

In Fig. 4, both the car rope pulley 6 and the counterweight rope pulley 7 are disposed in identical positions so that their middle planes of rotation are parallel to each other and at an angle to the middle plane of rotation of the traction sheave 5. The drive motor 8 is placed in an inclined position so that the middle plane of rotation of the traction sheave 5 is at an angle to the side wall 14 of the elevator car and the shaft wall whereas the middle planes of rotation of the car rope pulley 6 and counterweight rope pulley 7 are parallel to the side wall 14 of the elevator car and the shaft wall.

The invention is not restricted to the examples of its embodiments described above, but many variations are possible within the scope of the inventive idea defined in the claims.

## CLAIMS

1. Traction sheave elevator in which an elevator car is suspended on hoisting ropes by means of a diverting pulley, characterised in that the diverting pulley is mounted on a side of the elevator car.
2. Traction sheave elevator as defined in claim 1, characterised in that the hoisting machine of the traction sheave elevator is located in the elevator shaft.
3. Traction sheave elevator according to claim 1, to a top structure, characterised in that
  - car guide rails (1) disposed in the elevator shaft in a vertical direction;
  - elevator car (2) designed to move along the car guide rails;
  - counterweight guide rails (3) disposed in the elevator shaft on the same side of the elevator car as the car guide rails;
  - a counterweight (4) designed to move along the counterweight guide rails;
  - an upper rope pulley (5) mounted on a fixed top structure in the upper part of the elevator shaft;
  - a car rope pulley (6) connected to the elevator car;
  - a counterweight rope pulley (7) connected to the counterweight;
  - a drive motor (8) disposed in the elevator shaft to drive one of the rope pulleys; and
  - a rope (9), whose first end is attached to a fixed top structure in the upper part of the elevator shaft on the same side of the elevator car with the car and counterweight guide rails, from where the rope is passed via the counterweight rope pulley,

upper rope pulley and car rope pulley; and whose second end is attached to a fixed top structure;

- the second end (11) of the rope (9) is attached to a fixed top structure on the same side of the elevator car as the first end (10); and the car rope pulley (6) is rotatably mounted with bearings at the side of the elevator car (2) on the same side of the elevator car as the car and counterweight guide rails.

10 4. Elevator as defined in any one of claims 1 - 3, characterised in that the car guide rails (1) and counterweight guide rails (3) are attached to each other and to the wall (12) of the elevator shaft, disposed in parallel directions relative to each other  
15 and side by side so that the counterweight guide rails remain between the wall of the elevator shaft and the car guide rails.

5. Elevator as defined in any one of claims 1 - 4,  
20 characterised in that the distance between the counterweight guide rails (3) is equal to the distance between the car guide rails (1).

6. Elevator as defined in any one of claims 1 - 5,  
25 characterised in that the upper rope pulley (5) is a drive wheel connected to the drive motor; and that the drive motor is mounted on the car guide rails (1) and/or counterweight guide rails (3).

30 7. Elevator as defined in any one of claims 1 - 6, characterised in that it comprises an L-shaped frame structure (13) attached to the car, extending on the side wall (14) of the elevator car on that side where the car guide rails (1) and counterweight guide rails  
35 (3) are located and under the bottom (15) of the elevator car, the car rope pulley (6) and the guide ele-

ments (16) acting together with the car guide rails (1) being connected to said frame structure.

8. Elevator as defined in any one of claims 1 - 7,  
5 characterised in that the car rope pulley (6) is placed in the lower part of the elevator car near its bottom (15).

9. Elevator as defined in claim 7 or 8, character-  
10 ised in that the car rope pulley (6) is disposed inside the space defined by the elevator car (2) and the frame structure (13).

10. Elevator as defined in any one of claims 1 - 9,  
15 characterised in that a vertical tangent to the upper rope pulley (5) is substantially aligned with a vertical tangent to the counterweight rope pulley (7), the rope portion between these pulleys thus being substantially vertical.

20  
11. Elevator as defined in any one of claims 1 - 10, characterised in that a vertical tangent to the upper rope pulley (5) is substantially aligned with a vertical tangent to the car rope pulley (6), the rope por-  
25 tion between these pulleys thus being substantially vertical.

12. Elevator as defined in any one of claims 1 - 11, characterised in that the middle plane of rotation of  
30 the counterweight rope pulley (7) is parallel to the middle plane of rotation of the car rope pulley (6); and that the middle plane of rotation of the upper rope pulley (5) is at an angle to the middle planes of rotation of the car rope pulley and counterweight rope  
35 pulley.



13. Elevator as defined in claim 12, **characterised** in that the middle plane of rotation of the car rope pulley (6) is parallel to the side wall (14) of the elevator car (2).

5

14. Elevator as defined in claim 12, **characterised** in that the middle plane of rotation of the car rope pulley (6) is at an angle to the side wall (14) of the elevator car (2).

10

15. Elevator as defined in any one of claims 1 - 14, **characterised** in that the drive motor (8) is a permanent magnet synchronous motor and that the upper rope pulley (5) is integrated with the rotor of the motor.

15

16. Elevator car, **characterised** in that the elevator car comprises a diverting pulley placed on one of the sides of the car for suspending the car on hoisting ropes.

20

17. Method for suspending an elevator car on hoisting ropes, **characterised** in that the elevator car is provided with a diverting pulley placed on one side of the elevator car, a loop opening in an upward direction is formed in the hoisting ropes and the elevator car is suspended in this loop by the diverting pulley mounted on its side.

25

18. Use of a diverting pulley mounted on one side of an elevator car for suspending the elevator car on hoisting ropes.

30

19. Use as defined in claim 18, **characterised** in that the elevator car is part of a traction sheave elevator without machine room.

35

1/2




Fig 1

2/2




Fig 2




Fig 3

## INTERNATIONAL SEARCH REPORT

International Application No  
PCT/FI 00/00049

**A. CLASSIFICATION OF SUBJECT MATTER**  
IPC 7 B66B11/08

According to International Patent Classification (IPC) or to both national classification and IPC

**B. FIELDS SEARCHED**

Minimum documentation searched (classification system followed by classification symbols)  
IPC 7 B66B

Documentation searched other than minimum documentation to the extent that such documents are included in the fields searched

Electronic data base consulted during the international search (name of data base and, where practical, search terms used)

**C. DOCUMENTS CONSIDERED TO BE RELEVANT**

Category *	Citation of document, with indication, where appropriate, of the relevant passages	Relevant to claim No.
P, X	EP 0 953 538 A (TOKYO SHIBAURA ELECTRIC CO) 3 November 1999 (1999-11-03)	1-3, 8, 16-19
Y	column 18, line 9 - line 21; claims; figures 11, 16	4-6
A		7, 9-12
Y	EP 0 631 967 A (KONE OY) 4 January 1995 (1995-01-04)	4-6
A	cited in the application the whole document	1, 16-18
A	EP 0 849 209 A (OTIS ELEVATOR CO) 24 June 1998 (1998-06-24)	1, 16-18
	column 3, line 25 - line 27; figure 1	



Further documents are listed in the continuation of box C.



Patent family members are listed in annex.

\* Special categories of cited documents:

"A" document defining the general state of the art which is not considered to be of particular relevance

"E" earlier document but published on or after the international filing date

"L" document which may throw doubts on priority claim(s) or which is cited to establish the publication date of another citation or other special reason (as specified)

"O" document referring to an oral disclosure, use, exhibition or other means

"P" document published prior to the international filing date but later than the priority date claimed

"T" later document published after the international filing date or priority date and not in conflict with the application but cited to understand the principle or theory underlying the invention

"X" document of particular relevance; the claimed invention cannot be considered novel or cannot be considered to involve an inventive step when the document is taken alone

"Y" document of particular relevance; the claimed invention cannot be considered to involve an inventive step when the document is combined with one or more other such documents, such combination being obvious to a person skilled in the art.

"&" document member of the same patent family

Date of the actual completion of the international search

31 May 2000

Date of mailing of the international search report

13/06/2000

Name and mailing address of the ISA

European Patent Office, P.B. 6816 Patentlaan 2  
NL - 2280 HV Rijswijk  
Tel. (+31-70) 340-2040, Tx. 31 651 epo nl,  
Fax: (+31-70) 340-3016

Authorized officer

Salvador, D

# INTERNATIONAL SEARCH REPORT

Information on patent family members

International Application No

PCT/FI 00/00049

Patent document cited in search report		Publication date	Patent family member(s)	Publication date
EP 0953538	A	03-11-1999	JP 11310372 A CN 1233583 A	09-11-1999 03-11-1999
EP 0631967	A	04-01-1995	FI 941719 A,B, FI 932977 A AT 160759 T AT 179955 T AT 178028 T AU 669070 B AU 6595794 A BR 9402573 A CA 2126492 A,C CN 1105337 A,B DE 9422186 U DE 9422290 U DE 69407100 D DE 69407100 T DE 69417454 D DE 69417454 T DE 69418496 D DE 69418496 T DE 779233 T DE 784030 T DK 631967 T EP 0779233 A EP 0784030 A EP 0890541 A EP 0957061 A ES 2111208 T ES 2132822 T ES 2130731 T GR 3026157 T GR 3030137 T GR 3030680 T JP 2593288 B JP 7010434 A SG 45255 A SI 631967 T SI 784030 T SI 779233 T US 5429211 A AT 184572 T AU 679983 B AU 6590794 A BR 9402574 A CA 2126259 A,C CN 1105339 A,B DE 69420626 D DE 69420626 T EP 0631966 A ES 2135510 T FI 942432 A,B, JP 2889125 B	29-12-1994 29-12-1994 15-12-1997 15-05-1999 15-04-1999 23-05-1996 05-01-1995 14-03-1995 29-12-1994 19-07-1995 24-09-1998 28-10-1999 15-01-1998 02-04-1998 29-04-1999 08-07-1999 17-06-1999 09-09-1999 09-04-1998 09-04-1998 02-06-1998 18-06-1997 16-07-1997 13-01-1999 17-11-1999 01-03-1998 16-08-1999 01-07-1999 29-05-1998 31-08-1999 30-11-1999 26-03-1997 13-01-1995 16-01-1998 28-02-1999 30-06-1999 31-08-1999 04-07-1995 15-10-1999 17-07-1997 05-01-1995 14-03-1995 29-12-1994 19-07-1995 21-10-1999 30-12-1999 04-01-1995 01-11-1999 29-12-1994 10-05-1999
EP 0849209	A	24-06-1998	US 5899300 A JP 10182041 A	04-05-1999 07-07-1998